



DETENT-ACTION SWITCHES

ELECTROSWITCH		DETENT SWITCH WORKSHEET	
FEATURES:		ROTARY ACTION:	
SERIES <input type="checkbox"/> 21 <input type="checkbox"/> 24 <input type="checkbox"/> 25 <input type="checkbox"/> 28 <input type="checkbox"/> 31A <input type="checkbox"/> 31B		<input type="checkbox"/> Maintained <input type="checkbox"/> Spring-return	
HANDLES <input type="checkbox"/> Oval Flush <input type="checkbox"/> Oval Shank <input type="checkbox"/> Pistol-Grip <input type="checkbox"/> Knurled <input type="checkbox"/> Other		CONTACTS: <input type="checkbox"/> Nonshorting Contacts break-before-make <input type="checkbox"/> Shorting Contacts make-before-break	
		SPECIAL FEATURES Panel Thickness _____ Maximum Depth Behind Panel Allowable _____ <input type="checkbox"/> Key Lockable Handle Key Removable in _____ Position (s) <input type="checkbox"/> Key Operated (Series 31) Key Removable in _____ Position (s) <input type="checkbox"/> Solenoid Lock <input type="checkbox"/> Push-to-Turn <input type="checkbox"/> Waterproof Mount <input type="checkbox"/> Nameplate # _____	
SWITCH POSITION TABULATION (FRONT VIEW)			
TITLE ENGRAVING: _____		POSITION ENGRAVING	
DECK CONTACTS HANDLE END	POSITIONS		
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16			
SERIES 21, 24, 31		SERIES 25	
SERIES 28			
HANDLE POSITIONS			
DECK LAYOUTS			
Series 24 & 31 use numerical terminal markings Series 21, 25 & 28 use alphabetical terminal markings Indicate external terminal connectors required Switch is viewed from handle end * Terminal numbers are preliminary pending factory review and approval.			
MADE BY: _____	DATE: _____	COMPANY _____	
APPR BY: _____	DATE: _____	DWG NO. _____	
		SHEET _____ OF _____	